

HB T



Single-cylinder rod bottle jack 3000 to 32000 kg

FEATURES

- Heat-treated cylinder rod and screws
- Built-in overload valve
- Welded base (not screwed) to prevent the risk of leakage
- Wide base increases stability and safety
- Extension screw comes standard (except on HB320T model)
- Carrying handle included on models HB120T, HB200T and HB320T



HB320T



HB30T

HB60T

HB120T

HB200T



HB30T HB60T HB120T HB200T



Heat-treated cylinder rod and screws



Welded base (not screwed) to prevent any risk of leakage



Extension screw comes standard (except for HB320T)

| Model | | HB30T | HB60T | HB120T | HB200T | HB320T |
|--------------------|----|------------|-------------|-------------|-------------|-------------|
| Load capacity | kg | 3000 | 6000 | 12000 | 20000 | 32000 |
| Dimensions (LxWxH) | mm | 97x109x190 | 106x118x210 | 118x135x230 | 140x160x240 | 165x185x260 |
| Minimum height | mm | 190 | 210 | 230 | 240 | 260 |
| Elevation | mm | 118 | 125 | 150 | 150 | 160 |
| Adjustable height | mm | 60 | 70 | 80 | 60 | - |
| Net weight | kg | 2,95 | 3,7 | 6,5 | 9,7 | 17,8 |
| Gross weight | kg | 3,1 | 4,12 | 6,62 | 10,08 | 18,5 |