HPC



Horizontal plate clamp 1500 and 3000 kg

FEATURES

- Suitable for all sheet metal or plates up to 50 mm thick
- Designed to be used in pairs or bundles with an appropriate sling
- The use of a spreader bar is recommended to handle large sheet metal dimensions
- · Shackle and chain slings not included
- Load capacity up to 3000 kg



HPC30

kg

mm

mm

mm

mm

mm

mm

kg

HPC15

1500

0 - 50

50

210

130

100

30

4,3

HPC30

3000

0 - 50

50

236


203

110


36

6





HPC15



*	В
C	E

no
0
20
Œ.
.=
>
\geq
_
ion
0
H
G
ЯС
ÿ
75
0
8
2
~
-
2
any
ıke
- 0
_
nak
Ĕ
_
to
Ιţ
ght
=
.6
.Ξ
6
~
serves t
S
οí
~
_
ā:
, w
~
a
rese
N
0.1
~
=
-
7-
.0
fа
Jfa
nufa
nufa
anufa
nanufa
nanufa
manufacturer
e manufa
ne manufa
ρ
The manufa
The
The
The
The
ual. The
tual. The
tual. The
tual. The
tual. The
tual. The
tual. The
tual. The
ontractual. The
contractual. The
contractual. The
contractual. The
contractual. The
not contractual. The
not contractual. The
not contractual. The
not contractual. The
are not contractual. The
are not contractual. The
are not contractual. The
are not contractual. The
are not contractual. The
ions are not contractual. The
ions are not contractual. The
ions are not contractual. The
ions are not contractual. The
ensions are not contractual. The
ensions are not contractual. The
ensions are not contractual. The
ensions are not contractual. The
dimensions are not contractual. The
dimensions are not contractual. The
dimensions are not contractual. The
dimensions are not contractual. The
dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
and dimensions are not contractual. The
dimensions are not contractual. The

Model

Α

В

C

D

Weight

Opening

Load capacity