

HT250/NLC

Graphite
SERIES




Steel hand truck with fixed nose plate 250 kg

FEATURES

- Light, maneuverable and robust
- Ø 25 mm tube diameter
- Curved frame ideal for cylinders transport
- Premium wheels equipped with double sealed ball bearings provide excellent rolling performance
- Large-diameter wheels glide over curbs and ensure a smooth rolling



DOUBLE SEALED BALL BEARINGS



SCRATCH-RESISTANT HAMMER PAINT



REINFORCED WHEEL LOCK



4
MODELS
AVAILABLE



RG

High-quality pneumatic wheel with high density PP body



RSB

High-quality non-marking silent blue elastic rubber wheel



RSN

High-quality silent black elastic rubber wheel



RINC

High-quality puncture-proof non-marking silent foam wheel

Model		HT250/NLC-RG	HT250/NLC-RSB	HT250/NLC-RSN	HT250/NLC-RINC
Load capacity	kg	250	250	250	250
Overall length	mm	500	500	500	500
Overall depth	mm	430	430	430	430
Overall height	mm	1100	1100	1100	1100
Nose plate type		fixed	fixed	fixed	fixed
Nose plate width	mm	450	450	450	450
Nose plate depth	mm	150	150	150	150
Type of wheel tires		pneumatic	non-marking silent blue elastic rubber	silent black elastic rubber	non-marking silent puncture-proof foam
Type of wheel hub		high density PP	polyamide 6	polyamide 6	high density PP
Type of bearings		double sealed ball bearing	double sealed ball bearing	double sealed ball bearing	double sealed ball bearing
Wheels	mm	Ø260	Ø250	Ø250	Ø260
Weight	kg	12	12	12	12