









#### **FEATURES**

• Ideal for air conditioners, awnings or other loads

Strong and durable structure

• Max. lifting height of 5.40 m (depending on the model)

Great stability and maneuverability

Indoor/outdoor industrial use

• Easy transport

• Hand winch with automatic brake

No tool required

Delivered without accessories







Model		LP85	LP100	LP125	LP125R	LP150	LP250	LP280
Load capacity	kg	85	100	125	125	150	250	280
Lift height	mm	3300	4000	3500	4560	4500	5200	5200
Folded height	mm	1700	1650	1350	1450	1530	1750	1750
Number of extendable feet		3	3	4	4	4	4	4
Weight	kg	12,8	20,5	23,5	37	49,5	89	89











# **Options and accessories for LP** manual telescopic lifting tower



LP-BC07H

450 x 440 mm for LP85 and LP100

# LP-BC07M

for LP125, LP125R, and LP150



LP-BC05H

Small folding platform Large folding platform 750 x 440 mm for LP85 and LP100

### LP-BC05M

for LP125. LP125R. and LP150

#### LP-BC05M2

for LP250 and LP280



# LP-BC06H

Small top rack 450 x 450 mm for LP85 and LP100

# LP-BC06M

for LP125, LP125R, and **LP150** 



Large top rack 800 x 400 mm for LP85 et LP100

# LP-BC02M


for LP125, LP125R, and **LP150** 

## LP-BC02M2

for LP250 and LP280



for LP85 and LP100



LP-FCA06

for LP125, LP125R, and **LP150** 



LP-FCA07

Projector double support for LP125, LP125R, and **LP150** 



## LP-CV10H

V shape support for LP85 and LP100

# LP-CV10M

for LP125, LP125R, and LP150





LP-R2-710

Set of castors for LP100



**LP-R720** 

Set of castors for LP125 (including LP125R)





Three stabilizing feet for LP100



LP-CSP02

Four stabilizing feet





LP-RD-02 Set of Ø260 mm wheels for LP125R





for LP125