

PTE15N SC



Electric pallet truck with lithium battery and weighing precision scale 1500 kg

FEATURES

- Compact, robust, light and innovative design
- Fast battery recharge (only 2.5 hours)
- Easily replaceable battery
- PIN-code start-up
- Equipped with shock absorbing stabilizing rollers
- High precision weighing display
- Printer available in option



| Model | | PTE15NSC | |
|--|------------|--|-----|
| Trade name | | EDGE | |
| Drive | | electric | |
| Operator type | | pedestrian | |
| Rated capacity | Q (kg) | 1500 | |
| Weight with battery | kg | 180 | 185 |
| Wheel material | | polyurethane PU | |
| Drive wheel dimensions | mm | Ø210 x 70 | |
| Front roller dimensions | mm | Ø80 x 93 (single roller = 80 x 70) | |
| Stabilizing rollers dimensions | mm | Ø80 x 30 | |
| Standard lift | h3 (mm) | 115 | |
| Height of the tiller arm in running position min / max | h14 (mm) | 740 / 1162 | |
| Minimum fork height | h13 (mm) | 88 | |
| Overall length | l1 (mm) | 1560 | |
| Length to the front of the forks | l2 (mm) | 410 | |
| Overall width | b1 (mm) | 540 | |
| Fork dimensions | s/e/l (mm) | 64 / 182 / 1150 | |
| Width across forks | b5 (mm) | 562 | |
| Ground clearance | m2 (mm) | 21 | |
| Aisle width with pallet 800 x 1200 mm long | Ast (mm) | 2000 | |
| Turning radius | Wa (mm) | 1387 | |
| Travel speed without / with load | km/h | 4,4 / 4,2 | |
| Lift speed without / with load | mm/s | 22 / 15 | |
| Lowering speed without / with load | mm/s | 50 / 40 | |
| Permissible slope without / with load | % | 16 / 6 | |
| Service brake | | electromagnetic | |
| Traction motor, power S2 60 min | kw | 0,65 | |
| Lift motor rating at S3 10% | kw | 0,5 | |
| Battery voltage / nominal capacity K5 | V/Ah | 24 / 20 (24 / 30 or 24 / 36 in option) | |
| Battery weight | kg | 4,6 | |
| Noise level according to EN 12053, driver's ear | dB (A) | < 70 | |



IN OPTION

- Printer

