

HPESE25S



304 and 316 stainless steel premium manual pallet truck 2500 kg load capacity

FEATURES

- All metal parts are stainless steel to ensure long-lasting corrosion resistance
- Shock-resistant fully sealed monoblock pump with overload / pressure relief valve
- German hydraulic pump seals
- Three-position control lever: lift, neutral, lower
- Gradual or fast lading speed
- Nylon steering wheels and tandem fork rollers
- Robust and durable
- **304 stainless steel: Food processing equipment**
- **316 stainless steel: Food and chemical processing equipment**

STAINLESS STEEL
304: FOOD
316: FOOD & CHEMICAL



LARGE



STANDARD

SHORT

Specifications	Product Reference ♦ Model		HPESE25S304	HPESE25S316	HPESE25S316/800	HPESE25S316L
	Capacity	kg	2500	2500	2500	2500
	Stainless steel version		AISI 304	AISI 316	AISI 316	AISI 316
Weight	Weight	kg	74	74	63	76
Wheels	Nylon tandem rollers	mm	Ø 80x70	Ø 80x70	Ø 80x70	Ø 80x70
	Steering wheels	mm	Ø 200x50	Ø 200x50	Ø 200x50	Ø 200x50
Dimensions	Fork raised height	mm	200	200	200	200
	Fork lowered height	mm	85	85	85	85
	Fork length	mm	1150	1150	800	1150
	Width across forks	mm	520	520	520	685
	Fork width	mm	160	160	160	160